coverguard®

TECHNICAL DATASHEET

DIN Filter A2B2P3 (DIRIN

Ref. 6REF282

Cartridges DIN

A2B2P3



D

The +

RD40 universal thread connection according to EN 148-1

PURCHASE PACKAGING

Ref.	Size	Inner	Carton
6REF282NSI	-		36

SALES PACKAGING

Hangable individual box

DESCRIPTION

Combined filter A2B2P3 with universal thread DIN EN148-1 / RD-40, protection A2B2 against organic gases and vapors with a boiling point higher than 65 ° c, and inorganic gases and vapors. Can be used with all masks equipped with a universal connection system DIN EN148-1 / RD-40, and more specifically with ARNASYS (6FFD000) and EURMASK DIN (6EUR100NSI). Cartridge in ABS, filtration materials in activated carbon and pp non-woven (antifungal and antibacterial treated).

SECTORS

- Heavy & process industries
- Chemical & pharmaceutical industries
- Light Industries
- Infrastructure, building industry

APPLICATIONS

Organic gas and vapours with boiling point > 65°C.
Inorganic gases and vapours.
Toxic dusts.
For regular and prolonged use in a dangerous environment : industrial maintenance, fertilizer spreading, chemical industry, paint application, carpentry, wood industry, cement industry, metal cutting...

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57

TECHNICAL FEATURES

Shape	Universal filter	**Features**	A2B2P3
Weight	265 g		Breathing resistance :
Specifications	A2B2P3		* 30 l/min : 1,70 mbar.
Main risk	Respiratory protection from gases and vapours		* 95 l/min : 6,35 mbar.
		Service life	Can be used until abnormal breathing resistance and/or strange smell.
Color	Black		

STANDARD(S)

This equipment conforms to the personal protective equipment model covered by the EC type-examination certificate **PPE026AT2363**

Delivered by ITALCERT (0426) Viale Sarca- 336 20126 - MILANO Italy

CE EPI CAT. III

EN143:2000 / A1:2006	Particles filters
EN14387:2004 + A1:2008	Gas filters and combined filters

MAJ 21/02/2025

COVERGUARD
120 rue Michel Girer, 01390 Mionnay FRANCE - Tél +33 4 72 26 57 57