coverguard®

Printing Colors

Pantone 348 C

Folding Line

Outside Page

Front Cover

SAFETY GLASSES

coverguard® SAFETY DESIGNER

THETA

6THE0

FR Lunettes de protection THETA incolore, K, N - oculaire PC anti - UV, branches en Nylon + PC, résistance aux températures extrêmes.
• Branches flexibles et réglables
• Face inclinable
• Pont nasal antiglisse

EN THETA safety glasses clear, K, N - PC anti-UV lens, nylon + PC temples, resistance to extreme temperatures.
• Flexible and adjustable temple
• Inclination adjustment
• Anti-slip nose bridge

HU THETA víztiszta védőszemüveg , K, N - PC lencse UV elleni védelemmel, nejlon + PC szár. Szélsőséges hőmérsékletnek ellenálló.
• Rugalmas, önbeálló szárak
• Állítható dőlésszög
• Csúszásmentes orrnyereg

DE "Schutzbrille THETA klar, K, N - PC Sichtscheibe UV-Schutz, Nylon + PC Bügel, Widerstandsfähig gegen extreme Temperaturen".
• Biegsame, verstellbare Bügel
• Neigbare Gläser
• Rutschfester Nasensteg

IT Occhiali di protezione THETA incolore, K, N - lente PC anti UV, stanghetta in nylon + PC, resistente a temperature estremi.
• Stanghette flessibili e regolabili
• Inclinazione regolabile
• Ponte nasale antiscivolo

ES Gafas de seguridad THETA, transparentes, K, N - lente PC anti-UV, patillas nylon + PC, resistente a temperaturas extremas.
• Patillas flexibles y regulables
• Inclinación ajustable
• Puente nasal antideslizante

PT Óculos de proteção THETA incolor, K, N - lente PC anti-UV, haste nylon + PC, resistente a temperaturas extremas.
• Hastes flexíveis e ajustáveis
• Ajustamento de inclinação
• Ponte nasal antideslizamento

PL Okulary ochronne THETA bezbarwne, K - soczewka PC filtr UV, pałąk skroniowy nylon + PC, odporna na ekstremalne temperatury.
• Elastyczne i regulowane pałąki
• Regulacja pochyłu
• Antypoślizgowy mostek nosowy

RU Средство индивидуальной защиты органов зрения: защитные очки THETA - Сертифицирован согласно стандарту EN166 :2001, EN170 : 2002 или EN172 : 1994Обращайтесь к поставщику услуг по утилизации отходов по вопросам правильной утилизации предмета.
• гибкие и регулируемые дужки
• регулируемый наклон
• антискользящая носовая дужка

CE EN 166:2001

Worldwide Euro Protection
555 rue de la Dombes
01700 Les Echets
Miribel - France

CE EN 166 – EN 170
3-1.2 1SFTKN CE

5 450564 000469

v.20230103

EAC TP TC 019/2011

Certified by / Certifié par :
* SATRA Technology Europe Ltd
Bracetown Business Park, Clonee, D15 YN2P, Ireland
n°2777

La déclaration de conformité et disponible sur le site internet :
** https://wep.ovh/files/declaration_conformity/

FR ENTRETIEN DU PROTECTEUR OCULAIRE

Ce protecteur oculaire doit être conservé à l'abri du soleil et des produits chimiques abrasifs. L'oculaire doit être nettoyé à l'aide d'un chiffon doux trempé dans de l'eau tiède savonneuse. Le protecteur oculaire peut être nettoyé à l'aide de n'importe quel désinfectant ménager. Le marquage CE apposé sur cet article signifie le respect des exigences essentielles du règlement européen 2016/425 concernant les EPI. La déclaration de conformité est disponible sur le site internet : voir **.
MARQUAGE DE LA MONTURE : La monture porte les indications suivantes : "identification du fabricant", "numéro de la norme", "symbole de la résistance aux chocs", "champ d'application", "symbole CE".
-B Protecteur oculaire protégeant des particules à grande vitesse à incidence énergétique moyenne.
-T Protecteur oculaire protégeant des particules à grande vitesse à des températures extrêmes (55±2)°C et (-5±2)°C
-F Protecteur oculaire protégeant des particules à grande vitesse à faible incidence énergétique.
-S Monture répertoriée dans la catégorie Robustesse Générale Accrue.
-3 Protecteur oculaire protégeant des gouttelettes (lunettes de protection) et des projections de liquides (masques de protection).
-4 Protecteur oculaire protégeant des poussières d'une granulométrie de 5 µm.
-9 Protecteur oculaire protégeant des éclaboussures de métal fondu et de la pénétration de matières solides chaudes
-H Protecteur oculaire désigné pour de petites formes de têtes
Note: Si la lettre « B » ou « F » n'est pas suivie par la lettre "T", le protecteur oculaire doit être utilisé à TEMPERATURE AMBIANTE SEULEMENT.
MARQUAGE DE L'OCULAIRE Les oculaires portent les indications suivantes : "graduation de l'oculaire", "identification du fabricant", "classe optique", "résistance aux chocs", "symboles de résistance à la détérioration de surface et à la buée", "symbole CE"
1 Qualité optique classe 1 (port permanent)
2 Qualité optique classe 2 (port intermédiaire)
B Protecteur oculaire protégeant des particules à grande vitesse à incidence énergétique moyenne, uniquement à température ambiante.
F Protecteur oculaire protégeant des particules à grande vitesse à faible incidence énergétique, uniquement à température ambiante.
T Protecteur oculaire protégeant des particules à grande vitesse à des températures extrêmes (55±2)°C et (-5±2)°C
S Oculaire répertorié dans la catégorie Robustesse Générale Accrue.
K Oculaire résistant en surface aux rayures causées par des particules fines
N Oculaire antibuée
9 Protecteur oculaire protégeant des éclaboussures de métal fondu et de la pénétration de matières solides chaudes
⇨ Si la lettre « B » ou « F » n'est pas suivie par la lettre "T", le protecteur oculaire doit être utilisé à TEMPERATURE AMBIANTE SEULEMENT.
⇨ Quand différents oculaires et montures sont combinés, les règles suivantes doivent être observées : 1) Si la monture et l'oculaire ont des symboles F, B ou A différents, le niveau inférieur est attribué. 2) Une monture marquée 9 doit être munie d'une lentille marquée 9, en plus du marquage F, B ou A.
L'oculaire jaune indice 2-1.2 filtre 99% des rayons UV dangereux jusqu'à 380nm, mais peut modifier la perception des couleurs et ne protège pas de l'éblouissement solaire. L'oculaire marron, teinté, bleu miroir, miroir argent dont l'échelon CE est 5-2.5, généralement utilisé en Europe Centrale, offre une protection adéquate contre l'éblouissement solaire. L'oculaire miroir or clair dont le symbole est CE est 5-1.7 (filtre léger), offre une protection adéquate contre l'éblouissement solaire. L'oculaire vert marqué 3.3 offre une protection adéquate contre les rayons solaires. L'oculaire pour soudure vert indice 3 ou 5 protège des rayons infrarouges (IR) lors d'opérations de soudage et de brasage à un débit maxi des gaz de 200 litres/heure.
Les oculaires appartenant à la classe optique 3 ne conviennent pas pour une utilisation longue durée.
LISEZ ATTENTIVEMENT CE QUI SUIT : Non adapté à la vision directe du soleil. Ne protège pas contre les sources de lumière artificielles. Ce protecteur oculaire est résistant aux chocs, mais il ne protège pas contre tous les risques d'impact. Les matières composant ce protecteur oculaire peuvent provoquer des allergies cutanées chez les personnes sensibles à ces matières qui portent ce protecteur oculaire ; en cas de réaction allergique, consultez immédiatement un médecin. Toute rayure ou piqûre de l'oculaire diminuera la résistance aux chocs des protecteurs oculaires et leur qualité optique. Les oculaires rayés ou piqués doivent être remplacés immédiatement. Protection efficace assurée pendant 2 ans pour une utilisation dans des conditions normales et une bonne préservation. Le protecteur de l'oeil est livré monté et ne doit pas être démonté. Il ne dispose pas de pièces de rechange. Le protecteur oculaire doit être transporté dans son emballage d'origine. Les protecteurs de l'œil contre les particules lancées à grande vitesse portés sur des lunettes à branches ophtalmiques classiques peuvent provoquer des chocs, occasionnant ainsi un danger pour l'utilisateur.

EN MAINTENANCE OF EYEPROTECTOR

This eyeprotector should be stored away from direct sunlight and abrasive chemicals. The lens should be cleaned with a soft cloth in warm soapy water. The eyeprotector can be disinfected with any common household disinfectant. The CE marking put on this equipment signified that all specifications of the European regulation 2016/425 have been respected. The declaration of conformity is available on the web site: see **.
FRAME MARKING: The marking on the frame shows : "identification of the manufacturer", "number of the standard", "field of use", "symbol for impact resistance", "CE symbol".
-B indicates this eye protector provides protection against medium energy impact from high speed particles
-T Indicates this eye-protector provides protection against impact from high speed particles at extremes of temperature (55±2)°C and (-5±2)°C
-F indicates this eye protector provides protection against low energy impact from high speed particles
-S indicates the frame is classified as having General Increased Robustness
-3 indicates this eye protector provides protection for use against droplets (goggle) and splashes of liquids (face-shields)
-4 Indicates this eye protector provides protection for use against dust with a particle size of 5 µm.
-9 Indicates this eye-protector provides protection for use against splashes of molten metals and penetration of hot solids
-H Indicates this eye-protector is made for small head forms
Note : If the impact letter is not followed by the letter "T", then the eye-protector shall only be used at ROOM TEMPERATURE ONLY.
LENS MARKING: The lens are marked as follows : lens scale number, "identification of the manufacturer", "optical class", "impact resistance", "symbol for resistance to surface damage and fogging", "CE symbol".
1 indicates class 1 optical quality (permanent wear)
2 indicates class 2 optical quality (intermediate wear)
B indicates this eye protector provides protection against medium energy impact from high speed particles at room temperature only
T Indicates this eye-protector provides protection against impact from high speed particles at extremes of temperature (55±2)°C and (-5±2)°C
F indicates this eye protector provides protection against low energy impact from high speed particles at room temperature only
S indicates the lens is classified as having General Increased Robustness
K indicates the lens is resistant to surface damage by fine particles
N indicates the lens is resistant to fogging of oculars
9 indicates this eye-protector provides protection for use against splashes of molten metals and penetration of hot solids
⇨ If protection against high speed particles at extremes of temperature is required then the selected eye protector should be marked with the letter T immediately after the impact letter, i.e. FT, BT or AT. If the impact letter is not followed by the letter "T", then the eye-protector shall only be used at ROOM TEMPERATURE ONLY.
⇨ When different lenses and frames are combined, the following rules need to be observed :
1/ WARNING : if frame and lens have different certified symbol F, B or A, the lower level shall be assigned
2/ a frame marked with 9 must be fitted with a lens marked 9, in addition to F, B or A marking
Amber lens marked with shade number 2-1.2 filter out 99% of harmful UV radiation to 380nm, which may affect colour recognition and do not protect against sun glare. Brown, smoke, blue mirror, silver mirror lens marked with shade number 5-2.5, generally used in Central Europe, offers adequate protection against sun glare. Light gold mirror lens marked with shade number 5-1.7, a light filter, offers adequate protection against sun glare. Green lens marked with shade number 3-3 offers adequate protection against sun glare. Fire Mirror lens, Fire Red lens and Smoke Polarized lens marked with scale number 5-3.1 filters out intense sunlight and reduces sun glare. It is commonly used for outdoor applications in full sun condition. Dark Smoke lens marked with scale number 5-4.1 filters out intense sunlight and reduces sun glare but does not provide protection against infra-red. Welding lens marked 3 or 5 offers protection against Infra Red Radiation (IR) during cutting and braze welding operations to a maximum gas flow rate of 200 litters/hour.
Oculars belonging to the optical class 3 are not fitted for a long lasting use.
PLEASE PAY ATTENTION TO THE FOLLOWING: Not for the direct viewing of the sun. Not for protection against artificial light sources.
The eye-protector is impact-resistant but it will not protect against all impact hazards. Warning : the materials used in this eye protector may cause an allergic reaction to the skin of susceptible wearers; if any reaction is observed, doctor's advise should be immediately sought. Scratching or pitting of lens will reduce the eye protector's impact resistance and optical quality. Warning : scratched or pitted lens should be immediately replaced. Under normal usage and correct storage this product should offer sufficient protection for 2 years. The eye protector is delivered assembled and must not be dismantled. It has no spare parts. The eye protector should be transported in the bag that it was originally supplied in. Warning : Impact can be transmitted to prescription spectacles if worn underneath eye protectors.
This model is certified by : *

HU TÁJÉKOZTATÓ a Lux Optical védőszemüvegek rendeltetésszerű használatához

DE Wartung des Augenschutzes

IT Manutenzione del protettore oculare

ES MANTENIMIENTO DEL PROTECTOR OCULAR

PT Manutenção dos protectores oculares

RU уководство по эксплуатации
Средства индивидуальной защиты глаз: очки защитные

PL INSTRUKCJA UŻYTKOWANIA OKULARÓW OCHRONNYCH

NL ONDERHOUD AAN OOGBESCHERMING

RO ÎNTREȚINEREA OCHELARILOR DE PROTECȚIE

Back Cover

Inside Page

SR Одржавање заштитних наочара

AR العين حامي صيانة

DK BRUGSANVISNING TIL BESKYTTELSESBRILLE

CZ SK DRŽBA CHRÁNIČE

GR ΟΔΗΓΙΕΣ ΣΥΝΤΗΡΗΣΗΣ ΓΥΑΛΙΩΝ ΠΡΟΣΤΑΣΙΑΣ

BG ПОДДРЪЖКА НА ЗАЩИТНИТЕ СРЕДСТВА ЗА ОЧИТЕ

TR GÖZ KORUMA GERECİNİN BAKIMI

ET KAITSEPRILLIDE KASUTUSJUHEND

LV Acu aizsargu lietošanas instrukcija

LT AKIŲ APSAUGINĖS PRIEMONĖS PRIEŽIŪRA

UA Зміст засобу захисту очей.

FI SUOJALASIEN HOITO

HR UPORABA ŠTITNIK ZA OČI

SL VZDRŽEVANJE ZAŠČITE ZA OČI

BA ZAŠTITNO SREDSTVO ZA NAOČARE


Filename :
(Back Side)

Artwork Spec

Brand / Customers :	coverguard® - Color UIS
Category:	SAFETY GLASSES
Item Ref :	UIS 6THE0
Created Date :	2021-03-03
Revised Date :	2023-01-03
Designer :	Andrew Wong
Remarks :	[2021-03-03] Revamp to COVERGUARD. * MUST combine the backside artwok for final printing.

Print Dimension :	(W) - 297 mm x (H) - 420 mm
Print Color :	1C + 1C
Finished Size :	approx. (w) - 70mm x (h) - 205 mm
Window Size :	n/a
Fold Line :	Ref to artwork --------
Remarks :	**Paper Materials / Printing Method / Effect :** Paper materials of Insert : Paper weight : Printing finishing :

Folding Method :



* MUST show the UIS front (with logo and barcode) in polybag backside after folded and packed into polybag.